

Extrusion Laminator

DYH-1000

Dry / Wet Laminating Machine

Multi-layer adhesive lamination process suitable for all types of paper, film and aluminum foil, laminate combinations with BOPP, CPP, PE, nylon and metallic films. All plastic film laminates exhibit excellent transparency and adhesion.



Features

- › Automatic tension control on winding system, dual axis rewinder.
- › Automatic dual axes, cutter does not require machine to stop.
- › All heater types available including oil, steam and electric, etc.
- › Pneumatic oven for high speed drying.
- › Electric system microcomputer controlled for high speed lamination throughout.



鼎沅機械企業有限公司
DING YUAN MACHINE CORP.



Features

- › Fully automatic tension control system via dual DC drive.
- › Motorized turret type rewinder, automatic flying splice operation.

Specifications

Model	DYH-1600	DYH-1000
Machine Speed	150 m/min	
Unwind Width	1100, 1300, 1600, 2000 mm (max)	
Rewind Width	1100, 1300, 1600, 2000 mm (max)	
Coating Method	Gravure & Special Coater	
Unwinding & Rewinding Dia	ø600, ø800 m/m (max)	
Unwind Thickness	0.5 - 8 mil	
Rewind Thickness	3 - 10 mil	
Dryer Sec. Heat Source	Floating dryer system 4 zones 9 m, electric, steam, or gas dryer.	
Drive	AC inverter motor drive and AC servo; frequency, PLC and tension control. Material in/outfeed and winder with magnetic brake on coiler.	
Power	220V, 380V, 415V, 440V 50/60 Hz	